

# Petroleum

## RWPS13 Oil SAE R4



**Applications:** Hardwall hose for suction and delivery of oil in Hydraulic systems, resistant to weathering.

**Conforming Standards:** SAE J517, SAE 100 R4

**Temperature:** -40°C to +100°C

**Cover:** Black, smooth wrapped finish synthetic rubber

**Tube:** Black, synthetic rubber compound

**Reinforcement:** High strength synthetic cord plus embedded steel helix wire

Size	ID mm	OD mm	WP psi	BP psi	Bend mm	Vacuum %	Weight Kg/mtr
19	19.1	29.4	315	1245	120	90	0.52
25	25.4	34.9	255	1035	145	90	0.68
32	32.1	42.1	210	825	195	90	0.84
38	38.1	48.0	150	615	250	90	1.04
51	50.8	61.5	105	420	300	90	1.42
63	63.1	76.1	60	255	350	90	2.14
76	76.1	88.1	60	255	455	90	2.64
102	101.6	115.1	30	150	610	90	3.79

## RWPS20 MAXIMUS Marine Fuel Fill



**Applications:** Hardwall hose recommended for conveying diesel fuel in pleasure boats, self extinguishing cover, weathering resistant.

**Conforming Standard:** SAE J1527 A2

**Temperature:** -25°C to +110°C

**Cover:** Black, smooth wrapped finish rubber compound

**Tube:** Black, NBR rubber compound

**Reinforcement:** High strength synthetic cord plus embedded steel helix wire

Size	ID mm	OD mm	WP psi	BP psi	B Rad mm	Weight Kg/mtr
19	19.1	30.0	50	200	60	0.70
25	25.4	35.0	50	200	75	0.86
32	32.1	42.0	50	200	100	1.13
38	38.1	48.0	50	200	115	1.29
45	44.5	56.0	50	200	135	1.64
51	50.8	63.5	50	200	150	1.79
60	60.3	73.8	50	200	180	2.17