

RWWD23 ETNA MARINE EXHAUST

Hardwall hose specially designed for the marine industry for conveying wet exhaust fumes from engine intake and bilge exhaust Also, due to unique sizes, can be used in industrial applications.

Approved by Lloyds

- Tube:** Black, CR rubber compound
- Cover:** Black, corrugated wrapped finish CR flame retardant rubber compound
- Reinforcement:** High strength synthetic cord plus embedded steel helix wire
- Temperature:** -30°C to + 100°C
- Branding:**



Size	ID mm	WF psi	BF psi	BIRsd mm	Weight KgJmtr
25	25.4	25	75	110	0.48
30	30.1	25	75	120	0.52
32	32.1	25	75	130	0.65
38	38.1	25	75	150	0.75
42	41.3	25	75	160	0.80
45	44.5	25	75	170	0.87
51	50.8	25	75	180	1.07
57	57.9	25	75	190	1.20
60	60.3	25	75	195	1.28
63	63.5	25	75	200	1.30
70	69.9	25	75	235	1.38
76	76.1	25	75	250	1.46
90	88.9	25	75	330	1.73
102	101.6	25	75	410	2.06
114	114.3	25	75	500	2.30
127	127.0	25	75	560	2.58
152	152.6	25	75	680	3.18
203	203.2	25	75	995	5.52
254	254.0	25	75	1200	7.81
305	304.8	25	75	1550	10.75

DS-RWWD23

REV: OCTOBER 2020