

Chemical

Chemflex - SG



Applications: This range is designed to meet the suction and delivery applications for a wide range of chemicals.

Conforming Standards: AS2594

Conforms to AS2683, Type 1, Kind 1 for design parameters.

Construction: Multiple layers of polypropylene fabrics and films. Black with white spiral layline, inner wire is stainless steel and outer is galvanised steel.

Temperature: -20°C to +80°C

Hose Size (mm)	PRODUCT CODE	WP Kpa	BP Kpa	Bend Radius mm	Vacuum %	Safety Factor	Weight Kg/mtr
25	969-025	1000	6000	70	90	6:1	0.89
40	969-040	1000	6000	100	90	6:1	1.18
50	969-050	1000	6000	140	90	6:1	1.79
65	969-065	1000	6000	170	90	6:1	2.49
80	969-080	1000	6000	200	90	6:1	3.00
100	969-100	1000	6000	300	90	6:1	6.28

Chemflex - SS



Applications: This range is designed to meet the suction and delivery applications for a wide range of chemicals.

Conforming Standards: AS2594

Conforms to AS2683 Type 1, Kind 1 for design parameters.

Construction: Multiple layers of polypropylene fabrics and films. Black with white spiral layline, inner wire is stainless steel and outer is galvanised steel.

Temperature: -20°C to +80°C

Hose Size (mm)	PRODUCT CODE	WP Kpa	BP Kpa	Bend Radius mm	Vacuum %	Safety Factor	Weight Kg/mtr
25	969ASS-025	1000	6000	70	90	6:1	0.89
40	969ASS-040	1000	6000	100	90	6:1	1.18
50	969ASS-050	1000	6000	140	90	6:1	1.79
65	969ASS-065	1000	6000	170	90	6:1	2.49
80	969ASS-080	1000	6000	200	90	6:1	3.00
100	969ASS-100	1000	6000	300	90	6:1	6.28