BAT Industrial

# PRODUCT INFORMATION

## PGU-1501 SERIES
### HP GREY HOSE ASSY 3/8"

Wrapped surface grey high pressure washer hose assembly, manufactured to DIN EN857 2SC, size DN10 (3/8"). Working pressure 6000 PSI, burst pressure 18000 PSI. Working temperature 155 °C, outside diameter 17 mm ± 0.2. MSHA IC-285 approved. Fitted with Maximus layline marking.

- **Tube:** High strength synthetic rubber.
- **Reinforcement:** Two layers of high strength steel wire mesh.
- **Cover:** Anti-abrasive synthetic rubber, resistant to oils, fuels and atmospheric conditions.
- **Temperature:** Working temperature up to 155 °C.
- **Bend Restrictor:** Includes a red bend restrictor (19.5 mm).
- **Branding:** Maximus layline marking.
- **Applications:** Mineral and biological oils, water-glycol based fluids, water and lubricants.
- **Approvals:** MSHA and ISO 9001:2015, GOST and SGS approved.




| Model | Pressure | Fittings |
|---|---|---|
| HP GREY HOSE ASSY 3/8" x 10m | W.P 6000 PSI / B.P 18000 PSI | 3/8" BSPTM x BSPPF |
| HP GREY HOSE ASSY 3/8" x 15m | W.P 6000 PSI / B.P 18000 PSI | 3/8" BSPTM x BSPPF |
| HP GREY HOSE ASSY 3/8" x 20m | W.P 6000 PSI / B.P 18000 PSI | 3/8" BSPTM x BSPPF |
| HP GREY HOSE ASSY 3/8" x 25m | W.P 6000 PSI / B.P 18000 PSI | 3/8" BSPTM x BSPPF |
| HP GREY HOSE ASSY 3/8" x 30m | W.P 6000 PSI / B.P 18000 PSI | 3/8" BSPTM x BSPPF |
| HP GREY HOSE ASSY 3/8" x 60m | W.P 6000 PSI / B.P 18000 PSI | 3/8" BSPTM x BSPPF |

DS-PGU-1501 ISSUED: AUG 2026 REV: AUG 2026

1300 BATSALES
sales@batind.com.au
1300 228 725