

## PHFS15 Bacco

Suction and delivery of dregs, wines, liqueurs up to 30% alcohol, and alimentary liquids. The hose is very light and flexible and is resistant to crushing, abrasion, weathering, atmospheric agents and most other chemicals.

Tube: Transparent, plasticised PVC

Cover: Transparent, slightly corrugated plasticised PVC

Reinforcement: Anti-shock rigid red PVC spiral helix

-10°C to +60°C Temperature:

Conforming Standards: FDA Title 21 CFR Item 177.2600

European directive 90/128/CEE,

Classes A, B, and C for food contact

**USP Class VI** 



Size	ID mm	OD mm	WP psi	BP psi	B Rad mm	Vacuum %	Weight Kg/mtr
25	25.4	32.0	130	390	170	100	0.40
32	32.1	39.1	130	390	230	100	0.52
38	38.1	46.3	130	390	260	100	0.73
45	44.5	53.3	130	390	310	100	0.92
51	50.8	60.2	115	345	350	100	1.10
63	63.5	74.3	115	345	440	100	1.63
76	76.1	87.1	115	345	525	100	1.95
102	101.6	115.4	90	270	695	90	3.35
152	152.4	170.2	60	180	1300	85	6.40

ISSUED: APR 2016 **REV: MAY 2019** DS-PHFS15

**1300 BATSALES** sales@batind.com.au 1300 228 725