

Receiver

 Society
 Reference
 Address
 Phone
 Fax
 E-mail

From

 -
 -
 -

Item n° :

60153197

Model :

S4B-8 M 230 V OL

Inverter application : Allowed - min. 30Hz

Pump data

 MEI \geq 0,40

P2 nominal requested : 0.37 kW

Min. fluid temperature : 0 °C

Max. fluid temperature : 40 °C

Max. Ambient temperature :

Requested data

Flow : 0 l/min

Head : 0 m

Fluid : Water

Fluid Temperature : 20 °C

 Density : 62.315 lb/ft³

 Kinematic viscosity : 1.0769E-5 ft²/s

Vapor pressure : 2.2045 kPa

Hydraulic data (duty point)

Flow :

Head :

Efficiency :

NPSH :

Materials

Lower support AISI 304 microfuse

Impeller Technopolymer A / AISI 304



Diffuser Technopolymer A

Impeller Lock nut Stainless steel

Cable cover AISI 304 X5 Cr Ni 1810 UNI 6900/71

Shaft with rotor AISI 304 X5 Cr Ni 1810 UNI 6900/71

Filter Stainless steel

Curve tolerance according to ISO 9906

Weight : 25.794 lb

Motor data

Motor brand : TESLA

Nominal power P2 : 0.37 kW

Rated voltage : 1~ 230 V 50 Hz

Nominal current : 3.5 A

Number of poles : 2

Rated speed : 2800 rpm

Degree of protection : IP 68

Dimensions in mm

DNM	1"1/4 G-F				
H	647				
Ø	97				

Pump connection

Discharge side : 1" 1/4 G-F



DATA SHEET

03-07-2017

Page 4 / 9

DAB PUMPS S.p.A.
Via Marco Polo, 14 - 35035 Mestrino (PD), Italy
Tel. +39 049 5125000 - Fax +39 049 5125950
www.dabpumps.com

Receiver

From

Society
Reference
Address
Phone
Fax
E-mail

-
-
-

Motor Code :

Motor :

Motor: 4OL 0,37 kW 230 V M

Materials

Motor data

Motor brand : TESLA
Nominal power P2 : 0.37 kW
Rated voltage : 1~ 230 V 50 Hz
Nominal current : 3.5 A
Number of poles : 2
Rated speed : 2800 rpm
Degree of protection : IP 68
Inverter application : Allowed - min. 30Hz
Power factor : 0.9
Efficiency : 51 %
Cable section Ø mm² : 4x1,5
Cable length m : 1,7
Cooling flow :

Weight : 14.55 lb

Dimensions in mm

--	--	--	--	--	--



WATER • TECHNOLOGY

DERATING

03-07-2017

Page 5 / 9

DAB PUMPS S.p.A.
Via Marco Polo, 14 - 35035 Mestrino (PD), Italy
Tel. +39 049 5125000 - Fax +39 049 5125950
www.dabpumps.com

Receiver

Society
Reference
Address
Phone
Fax
E-mail

From

-
-
-

Motor Code :

Motor: 4OL 0,37 kW 230 V M



PERFORMANCE CURVES

03-07-2017


Page 8 / 9

DAB PUMPS S.p.A.
Via Marco Polo, 14 - 35035 Mestrino (PD), Italy
Tel. +39 049 5125000 - Fax +39 049 5125950
www.dabpumps.com

	Receiver	From
Society	-	-
Reference	-	-
Address	-	-
Phone		
Fax		
E-mail		

S4B-8 M 230 V OL

Curve tolerance according to ISO 9906



Hydraulic data (duty point)

Suction side :	Discharge side : 1 " 1/4 G-F --	Flow : 0 l/min	Head : 0 m	Rated speed : 2800 rpm
Project	Project ID	Created by	Created on 03-07-2017	



DIMENSIONAL DRAWING

03-07-2017

Page 9 / 9

DAB PUMPS S.p.A.
Via Marco Polo, 14 - 35035 Mestrino (PD), Italy
Tel. +39 049 5125000 - Fax +39 049 5125950
www.dabpumps.com


Receiver

From

Society
Reference
Address
Phone
Fax
E-mail

-
-
-

S4B-8 M 230 V OL



Dimensions in mm						Pump connection
1	DNM	1"1/4 G-F				Suction
2	H	647				
3	\varnothing	97				
						Discharge 1" 1/4 G-F --

Project	Project ID	Created by	Created on 03-07-2017
---------	------------	------------	---------------------------------