

# reflex

Thinking solutions.

**PRODUCT PROFILE**  
REFIX DC 140 BLUE PRESSURE VESSEL 10 BAR  
REF-DC140 – 806054



Reflex tanks are ideally suited for a wide range of applications including booster systems, bore hole systems, sprinklers, irrigation systems, HVAC, thermal expansion and water hammer arresting.

## Features

- Manufactured in the EU, diaphragm according to DIN EN 13831 part 3
- 304 Stainless Steel water connection
- Corrosion resistant for long life
- UV resistant epoxy coating with a minimum thickness of 30 micron in blue RAL5007
- Air valve with sealing cap eliminates leaks
- Food grade approved high-grade butyl membranes and bladders WRAS, ACS, AS/NZS4020
- 5 year tank replacement guarantee

## Characteristics

- Nominal volume: 140 L
- Useful volume max.: 126 L
- Continuous max. temperature: 70°C
- Continuous max. pressure: 10 bar
- Pre-charge: 4 bar
- Diameter: 480 mm
- Height: 997 mm
- Net weight: 29 kg
- System connection: G1
- Colour: Blue RAL 5007



CE WRAS APPROVED PRODUCT ACS

Distributed By:  
**WHITE**  
INTERNATIONAL  
www.whiteint.com.au  
www.whiteint.co.nz