## TITASEAL PTFE THREAD TAPE

SERIES

### Description

PTFE (Polytetraflouroethylene) tape is a non-adhesive tape for use with threaded fittings on all types of pipes, including gas and liquid carrying pipework, including potable water.

### **Applications**

PTFE tape can be used on pipe made from galvanised steel, iron, brass, copper, aluminum, stainless steel, polyethylene, polypropylene, PVC, CPVC, ABS or fibreglass.

It can also be used on pipes carrying the following materials: Diesel fuel oil, gasoline, alcohols, heating oils, hydraulic fluids, steam, water etc.

Store in a cool, dry conditions between 5°C and 25°C. Do not use on pipes, which contain liquid oxygen or flourine.

### **Specifications**

- Conforms to AS 1272-1974
- · AGA Approved Class III
- Rated working pressure of 2000Kpa
- · Temperature range 10°C to +200°C

### **Features**

- · Will not harden or crack on the joint.
- · Acts as a thread lubricant and anti-seize
- · Prevents electrolytic corrosion of threads
- · Non-toxic
- Non-flammable
- · Unlimited shelf life
- · Available in Grey, Yellow and Pink
- · Suitable for potable water
- Non flammable



Austworld PO Box 311 Ashmore City QLD 4214 P: 1300 780 430 F: 1300 780 441

E: info@austworld.com.au W: www.austworld.com.au





# TITASEAL PTFE THREAD TAPE



## Sizing Chart MM

	SIZE	COLOUR
M103	12MM X 0.1 X 10MTR	PINK
M104	12MM X 0.1 X 30MTR	PINK
M105	12MM X 0.1 X 10MTR	YELLOW
M106	12MM X 0.1 X 30MTR	YELLOW
M108	12MM X 0.1 X 10MTR	GREY



Austworld PO Box 311 Ashmore City QLD 4214 P: 1300 780 430 F: 1300 780 441

E: info@austworld.com.au W: www.austworld.com.au



